




09760 - FLESSIBILIZZANTE



800-750 ml +
200-250 ml

DESCRIPTION

Colourless additive to increase the flexibility of two-pack topcoats aimed to be applied on plastics.

USE

Add to the topcoat MACROFAN MAC41, to MACROFAN UHS CLEARCOATS and 2K FILLERS to be used on car plastic parts.

CHARACTERISTICS

It improves the film flexibility in case of application on flexible plastics.

APPLICATION

Add to MACROFAN MAC41 and to MACROFAN UHS CLEARCOATS as follows:

TOPCOAT / CLEARCOAT	750 or 800 parts
09760 FLESSIBILIZZANTE	<u>250 or 200 parts</u>
	1000 1000 parts

Catalyse the final mixture just as the base product not flexibilized.
Fillers must be flexibilized max. at 10%.

DRYING TIME

This plasticizer addition does not considerably affect the drying methods and times of the base product.

TECHNICAL DATA SHEET N° 0281-GB
UPDATED 12/2019

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.